



Batis | Gypsum boards and ceiling tiles

Behin Sazan No-Andish Sepahan Factory, known as the second large gypsum board producer in Iran, is located in Garmsar industrial zone. Its annual capacity of production amounts to 10 million square meters in its very first phase. The factory manufactures its products according to international Standard EN520, under the brand name BATIS.

■ Gypsum boards

These are gypsum cored boards, the surfaces and edges of which are covered with a special firm kind of paper. They are generally used in dry construction systems (such as separator walls, covering treatment walls and dropped ceilings).

Technical specifications

- Two regular (RG) and moisture resistant (MR) Types.
- Dimensions 2400 x 1200 mm.
- Thickness 9.5 and 12.5 mm.
- Produced in compliance with international standard EN520.

Features

- Easy installation.
- Sound, temperature and moisture insulated.
- Capable of being painted or wallpapered immediately after installation.
- Lightening the buildings.

Usages

- Dropped ceilings.
- Separating walls.
- Interior walls of the building.
- Prefabricated buildings.
- Alternative to traditional whitewashing.

■ Light steel sections (structures)

Structures play an important role in strength and longevity of integrated roofs and separating walls. Battis structures are produced from light galvanized steel sheets with U-L-F shaped sections through cold rolling method and out of the best galvanized sheets found in the country.

■ Sealant powder

Batis sealant is used for sealing gypsum coated plates. the putty is applied as a thin layer of 1 to 2 mm thickness and forms a reinforced and strong structure.

■ Ceiling tiles

Patterned gypsum tiles are applied mostly in movable, closed and decorative ceilings. Those with PVC coating are produced and offered to the market in 7 different designs and in two types: plain backed and aluminum backed tiles, the latter of which are used in places where there is a possibility of water spillage caused by sweating behind the tiles (such as the passage of utility pipes or in wet areas such as swimming pools).

Technical specifications

- Dimensions 600 x 600 mm.
- Thickness 7.5 mm.

Features

- Quick and easy installation.
- Beautiful appearance.
- Easy access to the home installations space.
- No more painting operations needed.
- Ease of maintenance.

Batis Gypsum Board

(Regular)



International Standard No: EN 520

Batis RG Gypsum Board

Code	Dimensions m	Thickness mm	Board Size	Boards per Pallet
200015	1.20 x 2.40	9.5	2.88	120
200016	1.20 x 2.40	12.5	2.88	90

Batis Gypsum Boards are Produced in two forms:
smooth edge (VK) and chamfered edge (Ak)



گچ برگ باتیس (ضد رطوبت)



International Standard No: EN 520

Batis MR Gypsum Board (Anti Humidity)

Code	Dimensions m	Thickness mm	Board Size	Boards per Pallet
200047	1.20 x 2.40	12.5	2.88	90

Batis Gypsum Boards are Produced in two forms:
smooth edge (VK) and chamfered edge (Ak)



Batis Ceiling Tile

Thickness: 7.5 mm



Gypsum Filler

Code	bag Weight	Bags per Pallet
200053	20	80



Batis Ceiling Tile

Thickness: 7.5 mm



**Batis Patterned PVC Coated
Gypsum Tile - 7.5mm**

Code	Design Name	Pieces	Dimensions cm	Package Size	Number per Pallet
91011	Plain (154)	60X60	10	3.6	520 Aluminum backed
90018	wicker (996)				
91012	Ruby (238)				
91013	Almas (239)				
91009	Cross Fisher (631)				
91008	Diamond (567)				
91010	Dew (975)				

